RHEEM 27 CONTINUOUS FLOW WATER HEATER

GAS	5.8 STAR	PEOPLE	DELIVERY	WARRANTY [1]
	★★★★★★	2 - 6	27 L/MIN	10 YEAR

FEATURES

- **5.8 Star energy efficiency** – good for the environment, and saves on energy costs
- **27 Litre/Minute continuous hot water delivery** – ideal for families and large homes[3,4]
- **Solar ready** – compatible with Solar systems, without the need for any additional fittings
- **Reduced water wastage** – reduced flow during start-up
- **Remote Temperature Controller options** for added convenience and safety
- 50°C models available, requiring no tempering valve[2]
- Commercial models available offering temperature delivery of up to **82°C**[2]
- 10 Year warranty[1]

WHY CHOOSE FROM THE RHEEM CONTINUOUS FLOW HOT WATER RANGE?

- Never runs out of hot water
- Range of capacities from 18 – 27Litres/Minute[3,4]
- Ability to deliver up to 54L/Minute by linking two units with the Rheem EZ Link system[4]
- Flamesafe® overheat protection
- Digital display for easy fault diagnosis and service
- Frost protected down to -20°C
- Compact size models, perfect for any location with limited space
- Full technical support through Rheem's National Service Network
- Available to suit Natural Gas or Propane

10 YEAR Rheem WARRANTY [1]

ENERGY EFFICIENT 5 STAR

EZ LINK SYSTEM

FROST PROTECTED

Qfactor™

SOLAR READY

Flamesafe®

RHEEM 27 CONTINUOUS FLOW WATER HEATER

CONTINUOUS FLOW HOT WATER WHEN YOU NEED IT

Continuous Flow water heaters deliver hot water that never runs out because they heat water when you need it, for as long as you need it. They work differently to traditional storage water heaters, only heating on demand rather than heating and storing water until needed. 5 Star energy efficient, Rheem Continuous Flow water heaters are good for the environment and they mount conveniently to the wall, taking up less space.

With a wide range of capacities, there is a Rheem Continuous Flow model for every budget and family.



MODEL	RHEEM 27 CONTINUOUS FLOW	
	OUTDOOR	
	876027NF/PF	874027NF/PF
	Natural Gas/ Propane	
Temperature (°C)	50	60
Gas Energy Rating	5.8 Stars	
Flow Rate (L/Min at 25°C rise)	27L/Min	
Minimum Operating Flow rate	2.0L/Min	
Gas Consumption (typical value)	200 MJ/h	
Dimensions (mm)		
Height A	600	
Width B	350	
Depth C	215	
Approx Weight (kg)	23	
Max. Water Supply Pressure	1000kPa	
Min. Water Supply Pressure	140kPa	
Cold Water Connection	R ¾/20	
Hot Water Connection	R ¾/20	
Gas Connection	R ¾/20	
Accessories		
Pipe Cover	299830	
Recess Box	299831	
Security Wall Mounting	299868	
Security Cage	299867	
Temp. Controllers		
Kitchen	299850	
Bathroom 1	299851	
Bathroom 2	299852	
Deluxe Temp. Controllers		
Kitchen	299858	
Bathroom 1	299859	
Bathroom 2	299860	

R&R Plumbing Supplies
PLUMBING PLUS
16 Stradbroke St., (P.O. Box 632)
TOOWOOMBA, QLD. 4350
Ph: (07) 4634 2955 Fax: (07) 4633 2707

[1] Continuous Flow Warranty Conditions
10 Years Parts & Labour on Heat Exchanger,
3 Years Parts & Labour warranty on all other components,
for domestic (non-commercial) installations.

[2] 60°C and higher temperature models and some applications require a tempering valve in accordance with AS 3500.4.

[3] For details of models refer to Rheem Continuous Flow Gas Hot water brochure.

[4] At 25°C temperature rise

® Registered Trademark of Rheem Australia Pty Ltd.
™ Trademark of Rheem Australia Pty Ltd.

The Australian Gas Association

Certified System Quality ISO 9001

AS 3498
WMKA00159

Rheem Australia Pty Ltd.
1 Alan Street, Rydalmere, New South Wales 2116, Australia
PO Box 6, Rydalmere, New South Wales 2116, Australia.

Materials and data are subject to change without notice.

MKT-BR-RD-27CF0509